

Attorney Docket No.: MP/147

UNITED STATES PATENT APPLICATION

OF

ALVARO J. LAGUNA

AND

CAREY V. CAMPBELL

FOR

AN IMPROVED BALLOON CATHETER AND METHOD OF MOUNTING SAME

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192

## TITLE OF THE INVENTION

AN IMPROVED BALLOON CATHETER AND METHOD OF MOUNTING SAME

5

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

10 The present invention relates to improved balloon catheter devices, and methods of making the same.

### 2. Description of Related Art

15 Balloon catheter devices are commonly used for a wide variety of medical procedures today, including temporarily occluding blood or other fluid flow, re-shaping of blood vessels or other body conduits, removing plaque or other obstructions from vessels, and/or delivering or positioning devices within vessels, such as intraluminal stent or stent-graft devices. With on-going advances in minimally invasive medical procedures, such balloon devices  
20 continue to grow in popularity and in scope of possible uses.

Traditionally, balloon devices have taken one of two general forms -- angioplasty balloons and embolectomy balloons. Angioplasty balloons have generally been constructed from relatively stiff material, such as poly(ethylene terephthalate) (PET), which can be safely inflated to relatively high internal  
25 pressures (such as on the order of 10 ATM (1.0 MPa) or more). These balloons generally inflate rapidly to a given maximum diameter and will undergo minimal additional enlargement upon introduction of additional pressure (until they burst under extreme pressures). These balloons are typically used where high pressure is desired, such as to fracture and/or compact hard plaque in a  
30 blood vessel or to deliver balloon expandable devices, such as stents. One drawback with stiff angioplasty balloons, however, is that upon deflation they tend to become a crinkled, flattened mass that have dimensions significantly larger than their initial introduction diameter -- making them more difficult to remove than to initially introduce. Additionally, these flattened devices in many

cases cause adverse interactions between themselves and the devices with which they are conjunctly used.

By contrast, embolectomy balloons are normally constructed from a highly elastomeric material, such as latex, which will enlarge steadily in diameter with a steady increase in internal pressure. These balloons typically are governed by the volume of fluid/liquid used to inflate them rather than an operating pressure, have much lower operating pressures (such as, typically on the order of about 2ATM (203 kPa) or less) and they tend to continue to grow in diameter upon further introduction of pressure until they ultimately burst.

These balloons are typically used in embolic procedures where soft material is repositioned in a vessel. Additionally, the balloon can be formed from a tacky material such as latex that can be used to adhere to soft plaque, thrombus or other undesirable material within a vessel and then withdrawn to remove the undesirable material. Although these balloons have low operating pressures, they do tend to deflate to diameters almost identical to their initial introduction diameters -- making them very easy to remove.

It has been a long desired goal to develop a balloon that can withstand the very high pressures required for angioplasty but also has the inflation and deflation characteristics of an embolectomy balloon. The combination of these properties was achieved with the invention of the balloon devices described in United States Patents 5,752,934 and 5,868,704 to Campbell, et al., and United States Patent Application 08/858,309 to Campbell, et al. These patents describe several important advances in balloon catheter constructions, including how to construct high pressure balloons from expanded polytetrafluoroethylene (PTFE) and an elastomer so as to exhibit steady growth with increasing pressure up to a pre-determined maximum diameter and then readily compact to virtually their initial introduction diameters for easy removal.

The Campbell et al. patents teach how to form a tubular sleeve from expanded PTFE tape and then coat the sleeve with an elastomer. The sleeve is then mounted on a catheter shaft in a manner that allows it to contain expansion liquid (either by mounting the sleeve over an expandable bladder (e.g., a latex or PET balloon) or by rendering the sleeve liquid-tight so as to allow it to serve as the bladder itself). The result is a unique balloon that combines high-pressure performance with compaction to near initial introductory diameter following inflation and deflation. Balloons made in

accordance with the Campbell et al. patents have excellent performance characteristics and are particularly suitable for delivery and/or deployment of balloon expandable devices, such as intravascular stents.

Despite the excellent performance characteristics of the Campbell et al. balloons, it is believed that further improvements are desirable in the balloons and their mounting techniques to make them easier to mount on catheter shafts. Further, it is believed that further improvements in balloon performance can be achieved by modifying the mounting techniques, such as to provide a controlled failure mechanism.

### **SUMMARY OF THE INVENTION**

The present invention is an improved method of forming and mounting a distensible balloon catheter, and sleeves used to construct such balloons. One embodiment of the method of the present invention comprises forming a distensible balloon sleeve with non-distensible ends. The sleeve is mounted on the catheter shaft at the non-distensible ends while retaining the distensibility of the balloon as a whole. This construction is easier to mount and more reliable in operation than previous mounting methods. Alternatively or additionally, the balloon may be mounted to the catheter shaft using non-distensible tape that also retains the distensibility of the operative portion of the balloon. The present invention is particularly adapted for use with expanded polytetrafluoroethylene (PTFE) balloons, such as those described in United States Patents 5,752,934 and 5,868,704 to Campbell, et al.

The mounting techniques of the present invention are further readily adapted to include other beneficial properties, such as inclusion of controlled failure mechanisms. These and other benefits of the present invention will be appreciated from review of the following description.

### **DESCRIPTION OF THE DRAWINGS**

The operation of the present invention should become apparent from the following description when considered in conjunction with the accompanying drawings, in which:

Figure 1 is a side elevation view of a balloon device made in accordance with the present invention shown, in an inflated orientation;

Figure 2 is a side elevation view of the balloon device of Figure 1, shown in a deflated orientation;

5           Figure 3 is an exploded side elevation view of a stepped end of a catheter shaft, an inner member, and a tubular sleeve used to construct a balloon in accordance with the present invention;

Figure 4 is an enlarged side elevation view of a sleeve mounted over a stepped end of a catheter shaft;

10           Figure 5 is the sleeve and stepped end of Figure 4 with a tape being wrapped around the sleeve to help attach it to the stepped end;

Figure 6 is the sleeve and stepped end of Figure 5 with the tape completely mounted over the sleeve on the end of the catheter shaft;

15           Figure 7 is a three-quarter elevation view of a further improved sleeve for use with the present invention;

Figure 8 is a three-quarter elevation view of an apparatus suitable for forming the sleeve of Figure 7;

20           Figure 9 is an enlarged three-quarter elevation view of a modified end of a sleeve for use with the present invention, the sleeve being provided with slits for providing controlled failure ruptures with the present invention;

Figure 10 is a side elevation view of a balloon device made in accordance with the present invention incorporating another embodiment of means to provide controlled failure with the present invention;

25           Figure 11 is a side elevation view of the balloon device of Figure 10 with the balloon over-inflated, which partially dislodges its mounting tape so as to uncover and begin to active the means to provide controlled failure ruptures;

Figure 12 is a side elevation view of the balloon device of Figure 11, showing the balloon deflating as a result of the controlled failure mechanism;

30           Figure 13 is a partial longitudinal cross-section view of another embodiment of a balloon device of the present invention; and

Figure 14 is a partial longitudinal cross-section view of yet another embodiment of a balloon device of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to improved methods of mounting a balloon such as that described in United States Patents 5,752,934 and  
5 5,868,704 to Campbell, et al. and United States Patent Application 08/858,309 to Campbell et al. (hereafter "Campbell et al. patents"), all incorporated by reference.

The Campbell et al. patents describe improved balloons that combine the ability to safely and predictably achieve high operating pressures with the  
10 ability to be introduced at a small initial profile, be fully inflated, and then deflated to nearly the same initial profile for ease of removal. The preferred balloon devices of the Campbell et al. inventions employ multiple wraps using a porous expanded polytetrafluoroethylene (PTFE) tape, such as one made in  
15 accordance with United States Patents 3,953,566 and 4,187,390, incorporated by reference, combined with an elastomeric material, such as a polyurethane, so as to seal the porous structure of the expanded PTFE and render it liquid-tight. The resulting structure can be formed into a tube and then mounted onto a catheter shaft, such as through adhesion using various adhesives and  
20 methods. In particular, the mounting methods contemplated by the Campbell et al. patents are described in United States Patent 5,752,934, for example, at: col. 9, lines 25-34; and col. 10, lines 38-44; and in United States Patent 5,868,704, for example, at: col. 10, line 60, to col. 11, line 3; col. 12, lines 4-13; and col. 14, line 17, to col. 15, line 8.

While these previous mounting methods function quite well, it has been  
25 determined that significant improvements are possible in increasing the speed and ease of mounting of tubular structures onto a catheter shaft in order to form a catheter balloon device. Referring to Figures 1 through 3, the present invention comprises an inflatable balloon 10, formed from a tubular sleeve 12 that is mounted onto a catheter shaft 14 and an inner member 16. The balloon  
30 10 is introduced in a compacted, deflated configuration 18, such as that shown in Figure 2, and then distended to a fully enlarged, inflated configuration 20, such as that shown in Figure 1.

The catheter shaft 14 preferably has a reduced diameter over a  
segment 22 adapted to receive the sleeve 12 so that a smooth transition 24 is  
35 formed between the catheter shaft 14 and the balloon following mounting, as is

shown in Figure 2. Figure 3 illustrates a beveled landing 26 that performs this function. By way of example, for a catheter shaft with an outer diameter of about 0.5 to 3.5 mm and a sleeve with a wall thickness of about 0.1 to 0.5 mm, a suitable landing 26 might have a diameter of about 0.5 to 2 mm. The difference in dimensions between the wall thickness and the reduced diameter of the landing can be accounted for by the addition of adhesive and a tape wrap, as is explained below. The length of the landing 26 in this embodiment might range from about 1 to 5 mm.

The sleeve 12 includes a first end 28 and a second end 30. The first end 28 of the sleeve 12 is attached to the landing 26. The second end 30 of the sleeve is attached to the inner member 16 at its distal (that is, "leading") end 32. The sleeve 12 should be constructed from a distensible material, such as an elastomer (e.g., silicone, latex, polyurethane, or from a composite of expanded PTFE and elastomer as described above) that allows the sleeve to be inflated and deflated within normal operating pressures without causing permanent unfolding or deforming of the balloon material. By the term "distensible," it is intended to define a balloon material with a structure that will change in one or more dimensions upon introduction of distention force. Preferably, the balloon material will compact to most or all of its previous dimensions upon removal of the force. In this manner, the balloon will deflate to a "wingless" diameter following inflation, instead of deflating to a flattened, "winged," structure that may be hard to remove, such as that formed by a conventional PET balloon.

*nothing's  
made*

It has been determined, however, that distensible material does not always mount successfully to a catheter shaft since the material may tend to separate from the catheter shaft and/or undergo damage during inflation. To address this problem, the present invention treats the ends 28, 30 of the sleeve 12 to render them non-distensible. By the term "non-distensible," it is intended to define a balloon material with a structure that is significantly less compliant under distention force than a distensible main body of the balloon and, preferably, material that will undergo little or no change in dimensions upon introduction of distention force.

As is explained in greater detail below, the ends may be rendered non-distensible through a variety of methods, including by: over-wrapping the ends with non-distensible material, such as a tape; attaching non-distensible

structures; coating or permeating the ends with a non-distensible material, such as a fluorinated ethylene propylene (FEP) or cyanoacrylate ester; and/or modifying the structure of the material to render it non-distensible, such as through heat (including laser) treatment. Other possible methods of rendering the ends non-distensible may include insert molding and injection molding.

Once the ends 28, 30 have been rendered non-distensible, the sleeve 12 may be readily mounted on the catheter to form a liquid-tight seal through a number of possible ways, such as through, but not limited to, application or tape, glue, heat bonding, mechanical swaging, or some combination of two or more of these mounting methods. The preferred method of mounting is described below with reference to Figures 4 through 6.

Figure 4 illustrates a sleeve 12 positioned over a landing 26 on a catheter shaft 14. The sleeve 12 and landing 26 should be proportioned so that the sleeve fits closely over the landing, with a clearance 32 of about 0.06 mm or less. Preferably, the sleeve 12 fits snugly over the landing 26, with virtually no clearance, so as to resist separation between the sleeve 12 and the catheter shaft 14 upon application of tension on the sleeve 12. An adhesive may be applied to the landing 26 (and/or the interior of the sleeve 12) prior to mounting on the shaft to aid in forming a bond. Suitable adhesives include: UV cure adhesive, cyanoacrylate ester, epoxy, polyurethane, silicone, and melt adhesives such as fluorinated ethylene propylene (FEP). The preferred adhesive is a thin coating of cyanoacrylate ester adhesive applied to the full surface of the landing immediately prior to placing the sleeve 12 on the catheter shaft 14.

Once the sleeve 12 is positioned on the catheter shaft 14, a tape 34 is wrapped around the end 28, as is shown in Figure 5. Tension is preferably applied on both ends 36, 38 of the tape as it is wrapped into place. To hold the tape in place, an adhesive should be applied between the wrap layers, such as by applying a drop of cyanoacrylate ester between the layers during the wrapping. Once the tape 34 is completely wrapped around the end 28 to snugly compress the sleeve against the landing, adhesive should be applied to the ends 36, 38 to secure the ends in place, as is shown in Figure 6.

The tape 34 is preferably formed from a material that is essentially non-distensible in its longitudinal direction. A preferred tape comprises a tape of expanded PTFE having a width of about 1 to 10 mm, a thickness of about 0.01



to 0.02 mm, and a matrix tensile strength in its longitudinal direction of about 50 to 150 kpsi (345 to 1034 MPa) measured using a strain rate of 100% per minute .

A number of alternative mounting techniques can be employed without departing from the present invention. For example, instead of applying a separate adhesive to the tape during the wrapping process, adhesive may be applied to the tape before wrapping and later activated (such as through application of heat, ultra-violet or infrared light, solvent activation, pressure activation, etc.). One method is to apply a coating of a thermoplastic polymer, such as polyurethane, to the tape prior to wrapping and then applying heat to the wrapped end to melt the polyurethane coating and bond the wrapping into place. Mounting can also be achieved by directly welding the tape, the sleeve material itself (with or without a tape wrap), and/or the catheter material into a sealed bond between the catheter and the sleeve, whether by application of heat, solvent, or other means.

The choice of materials should be selected so that bonding may be achieved without adversely affecting component performance. For example, if a catheter shaft of PEBA is employed with a composite balloon of expanded PTFE and polyurethane, the bonding melt temperature should be about 160° and maintained below 180°C.

Other alternative mounting techniques may include: compression fitting ("swaging"); solvent welding, ultrasonic welding; laser welding; radio frequency ("rf") welding; etc.

As has been noted, the ends 28, 30 of the sleeve 12 are preferably rendered non-distensible prior to mounting. To accomplish this, a number of techniques can be applied. Figure 7 illustrates a sleeve 12 that has had a non-distensible tape 40 applied around its ends 28, 30. One effective technique is to place the sleeve on a mandrel and then apply the tape in the manner previously described with respect to the sealing technique described above with respect to Figures 4 through 6. The mandrel may then be removed once the ends have been properly treated.

Another technique is to heat treat the ends 28, 30 to reduce the material's distensibility and profile in the end regions. One preferred method is to employ an oven 42 with a contractible iris 44 as is shown in Figure 8. To treat a sleeve 12 of expanded PTFE and elastomer, as previously described,

the oven 42 should be set to about 70 to 165 °C. Again, the sleeve 12 should be temporarily mounted on a mandrel to hold it in a proper orientation during the heat-treating process. The iris 44 is closed around the sleeve and compressed under a compressive force for about 1 to 30 seconds.

5           Alternative methods for rendering the ends of the sleeve 12 non-distensible include addition of metal bands, shrink tubing, plastic bands, wire wrap, use of non-distensible materials at the ends of the balloon, etc. Profile reduction may also be achieved through internal material removal, such as through grinding, solvent, or laser removal, or through material thickness  
10       reduction at the ends by thinning through relative elongation (e.g., stretching) of the ends. Additionally, distensible material may be removed from the ends, with other, non-distensible, materials possibly being substituted in that area.

Formed in this manner, a balloon made in accordance with the present invention retains all of the properties previously described with respect to the  
15       previous Campbell et al. balloons, while being faster, easier, and more reliable to mount on a catheter shaft.

The present invention may be further refined to provide other beneficial properties. For example, the mounting technique may be modified to provide for controlled failure if the balloon is ever accidentally over-inflated to a bursting  
20       pressure. One concern with any balloon material is that if the balloon is over-pressurized and bursts in a patient's body, small fragments of the burst balloon may be difficult or impossible to recover – potentially leading to very serious health problems for the patient. In this respect, it would be desirable to provide a mechanism for a balloon to fail in a completely controlled manner if over-  
25       inflation ever occurs so that all fragments of the balloon remain together following rupture or to ensure failure of another sub-system of the device prior to rupture of the actual balloon material.

One such method of accomplishing controlled failure is to form one or more apertures through the sleeve 12 that will release pressure prior to the  
30       balloon bursting – causing a predictable and controlled pressure release that does not result in fragment formation. Figure 9 illustrates one such method of treating the sleeve 12 by forming one or more slits 46a, 46b in at least one of the ends 28 (and/or 30) that will be sealed under mounting tape 34 prior to failure but will uncover once the balloon becomes over-expanded. The slits  
35       may be formed at any point during construction, but are most easily applied

after the ends have been rendered non-distensible. This process of progressively exposing the slit is shown in Figures 10 through 12.

Shown in Figure 10 is another embodiment of a weakened section, in this instance a small oval hole 48 formed in end 30. During normal operation, the hole 48 is completely concealed under the mounting tape 34. However, if the balloon 10 is ever over-inflated, as is shown in Figure 11, the tape 34 will fold toward distal end 52, progressively uncovering hole 48. Once the hole 48 is uncovered, the inflation liquid, causing excessive pressure in the balloon, will begin leaking through the hole 48. In this manner the balloon can be prevented from exploding and fragmenting – allowing the failed balloon to be removed in one piece.

Other methods of providing controlled failure of the balloon include: weakening the wall (without fully penetrating it) through use of a cut through only part of the sleeve wall; weakening the wall in a predetermined location by altering its structure through use of a laser, heat, mechanical means, or chemical reaction; reinforcing the sleeve in all but certain segments that are intended to fail (such as through a coating process); controllably degrading the elastomeric component so that failure constitutes leaking through the balloon material rather than rupture; selecting an elastomer that fails at a desired failure diameter; etc.

Without intending to limit the present invention to the specifics described hereinafter, the following examples illustrate how the present invention may be made.

#### Example 1

A 7.62 mm wide length of porous expanded PTFE film is wrapped onto a 4.0 mm diameter metal mandrel at a pitch of about 2.54 mm per mandrel revolution so that about 3 overlapping layers cover the mandrel. Following this wrap, another 3 layers of the same film are applied over the first 3 overlapping layers, using the same pitch but in the opposite direction. This method of single-pass application is repeated a total of six times, so that finally, a total of 18 helical overlapping layers are applied onto the mandrel.

With the wrapping complete, the mandrel and overlying expanded PTFE film are placed in an air convection oven set at about 380°C for about 18

minutes to heat-bond the adjacent layers of film, then removed and allowed to cool. The resulting 4.0 mm inner diameter film tube formed from the helically wrapped layers of film is then removed from the mandrel.

5 The film tube is then tensioned longitudinally, simultaneously reducing in diameter and lengthening until it reaches approximately 4.5 times its length while on the 4.0 mm mandrel post heat-bonding. The tube is then coaxially fitted over a 3.8 mm diameter metal mandrel. This coaxial fitting is done carefully, ensuring that the diameter increase experienced by the film tube occurs in a consistent manner, and that the tube is not damaged. With the  
10 coaxial fitting complete, the film tube is measured to be approximately twice its length while on the 4.0 mm mandrel post heat-bonding. The film tube is then carefully removed from the 3.8 mm mandrel.

15 Removed from the 3.8 mm mandrel, a knot is created at one end of the film tube while a 3.0 mm metal tube is inserted coaxially into the other end of the film tube. The metal tube and the overlying film tube are then submerged into a 4% (4 g per 100 ml) solution of TT-1070A TECOTHANE® resin manufactured by Thermedics Inc. (Woburn, MA) in tetrahydrofuran manufactured by J.T. Baker (Phillipsburg, NJ). The metal tube and the overlying film tube are situated such that the knotted end of the film tube is  
20 submerged completely, but the open end of the film tube and the open end of the metal tube are not. In this manner, the TECOTHANE® solution is in direct contact with the outside of the film tube for approximately one minute. The metal tube and the film tube are then removed from the TECOTHANE® solution, and the film tube (still wet with solution) is then carefully removed from  
25 the metal tube and allowed to dry at ambient temperature for approximately 30 minutes. Care is taken to avoid any folding of the film tube.

30 Next, the film tube is placed within an INSTRON® tensile test machine equipped with flat-faced jaws, and tensioned longitudinally at a rate of 200 mm/min until a load of 9.5 kg is achieved. Once this tension is achieved, the film tube is held at fixed length and subjected to heat from a hot air gun until the load indicator on the INSTRON® tensile testing machine reads 2.3 kg. The heat is such that it accelerates the force declination, but does not affect the TECOTHANE® material adversely. The upper jaw of the testing machine is then opened, and a 0.43 mm stainless steel wire is fitted coaxially within the  
35 longitudinally pulled film tube. The upper jaw is positioned such that it fully

engages the film tube, but not the resident wire, and closed. The film tube is then subjected to heat from the hot air gun and tensioned longitudinally again, at a rate of 200 mm/min, until a load of 8.7 kg is achieved. Once this tension is achieved, the film tube is again held at fixed length, with continued heat from the hot air gun, until the load indicator on the INSTRON® tensile testing machine reads 3.5 kg. The ends of the film tube are then secured to the wire to prevent longitudinal shrinkage, and the film tube and wire assembly are removed from the tensile test machine.

Additional expanded PTFE film is then helically applied to the outer surface of the film tube to inhibit wrinkling in the subsequent step. The securing means between the film tube and the underlying wire are removed. The tube is then compressed longitudinally, reducing the tube length to approximately 0.6 of the length just prior to this compression step. Care is taken to ensure a high degree of uniformity of compression along the length of the tube. The additional outer film is then removed from the longitudinally compressed film tube, and the film tube is cut at each end to expose approximately 2.0 cm of the wire underneath.

A blunt tipped needle with a female luer connector at one end, approximately 36 mm long, having 1.27 mm outer and 0.84 mm inner diameter, is inserted coaxially between the film tube and the 0.43 mm wire. A vacuum pump is then connected, by means of a male luer, to the female luer equipped needle at the end of the film tube, and the lumen of the film tube, via the needle, is subjected to negative pressure. The entire assembly consisting of the wire, film tube, and needle is then attached to a variable speed linear slide.

The slide is used to dip the assembly, with the vacuum pump running into a 10% (10 g per 100 ml) solution of TT-1070A TECOTHANE® resin manufactured by Thermedics Inc. (Woburn, MA) in tetrahydrofuran manufactured by J.T. Baker (Phillipsburg, NJ). The assembly is dipped to the point where about 5 mm of the film tube, covering the blunt needle, is within the solution. The assembly remains within the solution for approximately 30 seconds, after which the linear slide, set at a speed of 3.7 mm/sec is used to remove the assembly. The 3.7 mm/sec speed is chosen because it yields a continuous, uniform coating of solution on the surface of the film tube. Once completely removed from the solution, the assembly is disconnected from the linear slide and the vacuum pump, and allowed to dry at ambient temperature

for approximately 30 minutes. Care is taken to keep the assembly oriented in a vertical position to maintain the uniformity of the TECOTHANE® coating.

With the solution dry, the film tube is left with a thin coating of TT-1070A TECOTHANE® material on its outer surface. The portion of the film tube covering the blunt needle (along with the needle itself) is removed from the rest of the film tube. Likewise, a portion approximately 1.0 cm long is removed from the other end of the film tube. The remaining film tube portion is then carefully removed from the coaxially fitted 0.43 mm wire. Next, a small bevel cut is made at one end of the film tube. A 0.71 mm wire is used to push the point of the beveled end within the lumen of the coated film tube. The same wire is then carefully used to continue pushing the beveled end further and further within the lumen of the film tube, until finally, the beveled end passes completely through the length of the tube. The coating, which originally was on the outer surface of the tube, is now on the inner surface. This is done very carefully, so that no substantial lengthening of the tube occurs.

A portion of this balloon material is fitted coaxially onto a stepped steel mandrel which is wrapped manually with thin expanded PTFE film. Prior to being wrapped with film, the outer diameter of the large end of the mandrel is about 0.97 mm, and the outer diameter of the small end is about 0.71 mm. Once the mandrel is wrapped, the outer diameter of the large end of the mandrel is about 1.02 mm, and the outer diameter of the small end is about 0.74 mm. Isopropyl alcohol is used as a lubricant to ease the mounting of the balloon portion such that approximately 3.5 mm of material covers the large section of the stepped mandrel. The stepped mandrel, with the overlying balloon portion, is then placed into an air convection oven set at 80°C for approximately 5 minutes in order to evaporate the isopropyl alcohol. Upon removal from the oven, the outer diameter of the large (proximal) end of the balloon portion is about 1.37 mm, and the outer diameter of the small (distal) end is about 1.14 mm.

In an effort to reduce the outer diameters at both ends of the balloon material, a 3.5 mm section at each end of the balloon is treated within a heated contractible iris. The heated iris comprises of 15 metal wedges having a depth about of 6 mm, rotationally driven by a 20.0 mm diameter air piston with an input air pressure of about 241 kPa. The iris is adjusted to a temperature of 80°C, and a final contracted diameter of approximately 1.04

mm. A length of silicone tubing having an inner diameter of about 1.39 mm and an outer diameter of about 1.68 mm is fitted coaxially over the balloon material, and each end of the balloon (underneath the silicone tubing) is compressed for a 1 second cycle, and then a 7 second cycle. Following compression, the outer diameter of the proximal end of the balloon portion is 1.22 mm, and the outer diameter of the distal end is about 1.02 mm.

Next, small diameter reinforcing tubes are fabricated for the purpose of rendering the compressed ends of the balloon portion non-distensible. Since each end of the balloon portion is of different outer diameters, two reinforcing tubes are created. The reinforcing tube corresponding to the proximal end of the balloon portion is fabricated by helically wrapping 19.06 mm wide expanded PTFE film about a 1.24 mm diameter mandrel at a pitch of about 2.54 mm per mandrel revolution so that 7 to 8 overlapping layers covers the mandrel. Following these wraps, another 7 to 8 layers of the same film are applied over the first 7 to 8 overlapping layers, using the same pitch but in the opposite direction. This method of application is repeated a total of six times, so that finally, a total of 42 to 48 helical overlapping layers are applied onto the mandrel. With the wrapping complete, the mandrel and overlying expanded PTFE film are placed in an air convection oven set at 370°C for about 8 minutes. The reinforcing tube corresponding to the distal end of the balloon portion is fabricated in the same manner as that of the proximal reinforcing tube, but employs a 1.02 mm mandrel.

With the reinforcing tubes complete, a 3.0 mm long section is cut from each, forming two collars. Next, the outer surface of each compressed end of the balloon portion is treated with 7701 MEDICAL GRADE PRIMER manufactured by Loctite Corporation (Hartford, CT), and allowed to dry for approximately 15 minutes. A thin coating of 4981 INSTANT MEDICAL DEVICE ADHESIVE manufactured by Loctite Corporation (Hartford, CT), is then applied to the outer surface of the proximal end of the balloon portion, and the 3.0 mm long section of proximal reinforcing tube is fitted coaxially over the coated end. Any surplus adhesive is quickly wiped off, and digital pressure is applied to the reinforcing tube and the underlying balloon for approximately 1 minute. At this point, the outer diameter of the proximal end is about 1.47 mm. In an effort to reduce the outer diameter of the now reinforced proximal balloon end, the 3.5 mm long end region is covered by silicone tubing, inserted into the heated iris

as previously described, and compressed for a 1 second cycle, twice. The balloon end is then repositioned within the iris such that the outer most edge of the proximal end resided approximately 3 mm within the 6 mm deep iris, and compressed again for a 7 second cycle. These compression cycles result in a final proximal end diameter of about 1.37 mm. The procedure for adhesive application, fitting of the reinforcing tube and diameter compression is repeated for the distal end of the balloon. The diameter of the distal end after placement of the reinforcing tube is about 1.24 mm. The diameter of the distal end post compression is about 1.17 mm.

The balloon portion, with reinforced non-distensible ends is now finished and ready to be mounted onto a shaft assembly. To do so, the balloon portion is carefully removed from the underlying mandrel. The balloon portion and the mandrel are dowsed with isopropyl alcohol, and the balloon portion is carefully slid off the mandrel in the distal direction. Once off the mandrel, the balloon portion is inspected for damage. Any remnants of the film used to wrap the mandrel are removed from the interior of the portion, and any residual alcohol on the portion is allowed to evaporate.

A segment of extruded polyethylene tubing of about 0.71 mm inner diameter and about 0.94 mm outer diameter and approximately 29.0 cm in length is fitted coaxially onto a 0.69 mm diameter mandrel of slightly longer length such that the mandrel protrudes from each end of the tubing. A 3.5 mm length of one of the tubing ends is treated with 7701 MEDICAL GRADE PRIMER, and allowed to dry for approximately 15 minutes. A thin coating of 4981 INSTANT MEDICAL DEVICE ADHESIVE is then carefully applied to the same end, and the proximal end of the balloon portion is then fitted coaxially over the 0.69 mm mandrel and onto this region. Any surplus adhesive is quickly wiped off, and digital pressure is applied to the balloon end and the underlying tubing for approximately 1 minute. Great care is taken to ensure that no adhesive was applied to the 0.69 mm diameter mandrel. The outer diameter of the balloon end at this point is 1.42 mm. To reduce the outer diameter of the proximal balloon end now attached to the tubing, the 3.5 mm long end region is covered by silicone tubing, inserted into the heated iris as previously described, and compressed for a 1 second cycle, twice. The balloon end is then repositioned within the iris such that the outer most edge of the proximal end resided approximately 3 mm within the 6 mm deep iris, and



compressed again for a 7 second cycle. These compression cycles result in a final proximal end diameter of 1.27 mm. The 0.69 mm mandrel is then carefully removed from the tubing.

5 Next, a segment of extruded polyethylene tubing of 0.46 mm inner diameter and 0.58 mm outer diameter approximately 38 cm in length is fitted coaxially onto a 0.41 mm diameter mandrel of slightly longer length such that the mandrel protruded from each end of the tubing. The tubing, and the resident mandrel are then fitted coaxially within the lumen of the tubing to which the balloon is attached. This is achieved by sliding the smaller tubing and  
10 resident mandrel into the lumen of the larger tubing at its bare end, using isopropyl alcohol as a lubricant to aid the passing of the smaller tubing through the attached balloon. Care is taken to avoid damaging or significantly lengthening the attached balloon, and to ensure that the smaller tubing extended approximately 3 cm beyond the distal end of the balloon. The alcohol  
15 is allowed to evaporate, then a 3.5 mm length region of the smaller tubing extending beyond the distal end of the balloon is treated with 7701 MEDICAL GRADE PRIMER, and allowed to dry for approximately 15 minutes. A thin coating of 4981 INSTANT MEDICAL DEVICE ADHESIVE is then carefully applied to this region, and the balloon and attached tubing are then slid such  
20 that the 3.5 mm distal balloon end covered this region. Any surplus adhesive is quickly wiped off, and digital pressure is applied to the balloon end and the underlying tubing for approximately 1 minute. The outer diameter of the distal balloon end at this point is 1.19 mm. To reduce the outer diameter of the distal balloon end now attached to the inner tubing, the 3.5 mm long end region is  
25 covered by silicone tubing, inserted into the heated iris as previously described, and compressed for a 1 second cycle, twice. The balloon end is then repositioned within the iris such that the outer most edge of the distal end resides approximately 3.0 mm within the 6 mm deep iris, and is compressed again for a 7 second cycle. These compressions result in a final distal end  
30 diameter of 1.12 mm.

The balloon portion, successfully attached to the tubing in a coaxial configuration, defines a finished prototype balloon catheter, which is ready to be inflated. To affect a suitable inflation, a female luer fitting in a "Y" configuration is fitted with hydrostatic adapters at two of its three openings.  
35 This assembly is placed over the bare ends of the tubing such that one

hydrostatic adapter is situated on the small diameter tubing, and the other on the large diameter tubing. This placement leaves one of the openings of the "Y" fitting able to interface with a hand held inflation device commonly used to inflate balloon catheters, and allowed communication of inflation liquid between the inflation device and the annular space between the coaxially arranged large and small diameter tubing. The prototype balloon is inflated at room temperature steadily to approximately 1.6 MPa, and maintained at 1.6 MPa for approximately 1 minute. The balloon inflated consistently, exhibiting a relatively uniform outer diameter, with no leakage at either of the two ends at which the balloon is attached to the underlying tubing. The balloon is then deflated, and subsequently reinflated steadily until failure occurs due to leakage at the attachment sites. The failure occurs at approximately 3.0 MPa.

Example 2:

In an alternative embodiment, a portion of balloon material described in Example 1 is fitted coaxially onto a steel mandrel having an outer diameter of 0.71 mm. Isopropyl alcohol is used as a lubricant to ease the mounting of the balloon portion. The mandrel, with the overlying balloon portion, is then placed into an air convection oven set at 80°C for approximately 5 minutes in order to evaporate the isopropyl alcohol. Upon removal from the oven, the outer diameters of each end of the balloon portion are 1.00 and 1.10 mm.

To reduce the outer diameters at the ends of the balloon material, a 3.5 mm section at each end of the balloon is treated within a heated contractible iris as described in Example 1, using the same settings with exception of the air input pressure, which is adjusted to 103 kPa. As in the case of Example 1, a length of silicone tubing having an inner diameter of 1.39 mm, and an outer diameter of 1.68 mm is fitted coaxially over the balloon material. Each end of the balloon (underneath the silicone tubing) is then compressed for a 7 second cycle. Following compression, the outer diameters of the each end of the balloon portion are 0.95 and 1.01 mm.

Next, a small diameter reinforcing tube is fabricated for the purpose of dimensionally stabilizing the compressed ends of the balloon portion. The reinforcing tube is fabricated by helically wrapping 6.36 mm wide expanded PTFE film about a 1.04 mm diameter mandrel. The film is tensioned such that

it necked to a width of approximately 3.84 mm, and is applied at a pitch of 1.28 mm per mandrel revolution so that approximately 3 overlapping layers cover the mandrel. Following this, another 3 layers of the same film are applied over the first 3 overlapping layers using the same pitch, but in the opposite direction, so that a total of approximately 6 helical overlapping layers are applied onto the mandrel. With the wrapping complete, the mandrel and overlying expanded PTFE film are placed in an air convection oven set at 380°C for 7 minutes, cooled, and cut into 3.0 mm sections to form collars.

Each compressed end of the balloon portion is treated with 7701 MEDICAL GRADE PRIMER manufactured by Loctite Corporation (Hartford, CT), and allowed to dry for approximately 15 minutes. A thin coating of 4981 INSTANT MEDICAL DEVICE ADHESIVE, also manufactured by Loctite Corporation, is then applied to the outer surface of each end of the balloon portion, and 3.0 mm long sections of reinforcing tube are fitted coaxially over the each coated end. Any surplus adhesive is quickly wiped off, and digital pressure is applied to the sections of reinforcing tube and the underlying balloon for approximately 1 minute. At this point, the outer diameters of the ends are 1.08 and 1.07 mm. In an effort to reduce the outer diameters of the now reinforced balloon ends, the 3.5mm long end regions are covered by silicone tubing, inserted into the heated iris as previously described, and compressed for a 2 second cycle, then rotated approximately 90°, and compressed for another 2 second cycle. These compression cycles result in final end diameters of 1.07 and 0.99 mm.

A 1.07 mm diameter stainless steel wire is heated using a model 210-A hot air station manufactured by Beahm (Los Gatos, CA) set at 400 °C. The heated wire is used to flare a 3.5mm section of one end of extruded polyethylene tubing having a 0.76 mm inner and 1.04 mm outer diameter, approximately 21.0 cm in length. A thin coating of 4981 INSTANT MEDICAL DEVICE ADHESIVE was then carefully applied to the outer surface of one reinforced end of the balloon portion, and the flared end of the polyethylene tubing is then fitted coaxially over the 0.71 mm mandrel and onto this reinforced end. Any surplus adhesive is quickly wiped off, and digital pressure is applied to the tubing and the underlying balloon for approximately 1 minute. Great care is taken to ensure that no adhesive is applied to the 0.71 mm diameter mandrel. The outer diameter of the flared tubing end at this point is 1.22 mm.

In an effort to reduce the outer diameter of the tubing end now attached to the balloon, the 3.5 mm long end region is covered by silicone tubing, inserted into the heated iris, as previously described, and compressed for a 1 second cycle, then rotated approximately 90°, and compressed for another 1 second cycle.

5 These compression cycles result in a final tubing end diameter of 1.21 mm. The portion, the tubing, and the 0.71 mm mandrel are then dowsed with isopropyl alcohol, and carefully slid off the mandrel. Once off the mandrel, the portion and the tubing are inspected for damage, and any residual alcohol is allowed to evaporate. At this point, the balloon portion with non-distensible  
10 ends is ready to be mounted onto a shaft assembly.

Next, a segment of extruded polyethylene tubing of 0.46 mm inner diameter and 0.58 mm outer diameter approximately 38.0 cm in length was fitted coaxially onto a 0.41 mm diameter mandrel of slightly longer length such that the mandrel protrudes from each end of the tubing. The tubing and the  
15 resident mandrel are then fitted coaxially within the lumen of the tubing to which the balloon is attached. This is achieved by sliding the smaller tubing and resident mandrel into the lumen of the larger tubing at its bare end, using isopropyl alcohol as a lubricant to aid the passing of the smaller tubing through the attached balloon. Care is taken to avoid damaging the attached balloon,  
20 and to ensure that the smaller tubing extends approximately 1.5 cm beyond the free end of the balloon. The alcohol is allowed to evaporate, then a 3.5 mm length region of the smaller tubing extending beyond the free end of the balloon is treated with 7701 MEDICAL GRADE PRIMER, and allowed to dry for approximately 15 minutes. A thin coating of 4981 INSTANT MEDICAL DEVICE  
25 ADHESIVE is then carefully applied to this region, and the balloon and attached tubing are then slid such that the 3.5 mm balloon end covered this region. Any surplus adhesive is quickly wiped off, and digital pressure is applied to the balloon end and the underlying tubing for approximately 1 minute. The outer diameter of the balloon end at this point is 1.11 mm. To reduce the outer  
30 diameter of the balloon end now attached to the inner tubing, the 3.5 mm long end region is covered by silicone tubing, inserted into the heated iris, as previously described, and compressed for a 1 second cycle, three times, rotating the region approximately 60° between each. These compression cycles result in an end diameter of 0.93 mm.

A 0.97 mm diameter stainless steel wire is heated using a model 210-A hot air station manufactured by Beahm set at 400°C. The heated wire is used to flare a 3.5 mm section of one end of extruded polyethylene tubing having a 0.76 mm inner and a 1.04 mm outer diameter, approximately 1.0 cm in length.

5 A thin coating of 4981 INSTANT MEDICAL DEVICE ADHESIVE is then carefully applied to the reinforced end of the balloon portion attached to the smaller diameter tubing. The flared end of the polyethylene tubing is then fitted coaxially over the 0.41 mm diameter mandrel, the smaller tubing, and onto this reinforced end. Any surplus adhesive is quickly wiped off, and digital pressure  
10 is applied to the tubing and the underlying balloon for approximately 1 minute. Great care is taken to ensure that no adhesive is applied to the 0.41 mm diameter mandrel. The outer diameter of the flared tubing end at this point is 1.14 mm. In an effort to reduce the outer diameter of the tubing end now attached to the balloon, the 3.5 mm long end region is covered by silicone  
15 tubing, inserted into the heated iris as previously described, and compressed for a 1 second cycle, three times, rotating the region approximately 60° between each. These compression cycles result in a final tubing end diameter of 1.11 mm.

Unlike the embodiment illustrated in Figures 1 through 4, above, this  
20 embodiment of the present invention results in the balloon material being mounted inside the catheter shaft. This structure is illustrated in Figure 13. The catheter shaft 50 is flared at its end 52 and forms a collar 54 around balloon material 56. This unique construction further limits distention of end 58 of the balloon material 56 and forms a tight interference fit between the collar  
25 and the balloon under pressure.

The balloon material, successfully attached to the tubing in a coaxial configuration, defines a finished prototype balloon catheter, which is ready to be inflated. To affect a suitable inflation, a female luer fitting in a "Y" configuration is fitted with hydrostatic adapters at two of its three openings.  
30 This assembly is placed over the bare ends of the tubing such that one hydrostatic adapter is situated on the small diameter tubing, and the other on the large diameter tubing. This placement leaves one of the openings of the "Y" fitting able to interface with a hand held inflation device commonly used to inflate balloon catheters, and allows communication of inflation liquid between  
35 the inflation device and the annular space between the coaxially arranged large

and small diameter tubing. The prototype balloon is inflated at room temperature steadily until failure occurs due to leakage at the attachment sites. The failure occurs at approximately 1.4 MPa.

5           Example 3:

Still another example of attachment of a sleeve 60 of the present invention to a catheter shaft 62 is illustrated in Figure 14. In this Example, the sleeve 60 is mounted to the catheter shaft 64 as an end-to-end butt joint 66,  
10 similar to that previously described with respect to Figures 1 through 4 except that no landing is employed. The butt-joint 66 is believed to be easier to construct and employ for some applications. The butt-joint 66 may be held together with a tape wrap, as previously described, or through use of a collar 68, formed from a shrink tube plastic or similar material. Again, the collar 68 is  
15 preferably formed from an essentially non-distensible material to further limit distention of the sleeve 60 end 70 when the balloon is inflated.

It should be understood that the present invention may be modified and further refined without departing from its intended scope. In particular,  
20 materials and construction specifications may be readily changed to address specific application needs. For example, although the above description and examples are directed to coaxial catheter shafts, the present invention may also be applied to multi-lumen catheter shafts.

While particular embodiments of the present invention have been  
25 illustrated and described herein, the present invention should not be limited to such illustrations and descriptions. It should be apparent that changes and modifications may be incorporated and embodied as part of the present invention within the scope of the following claims.